

S/FTP 4Pairs cable-category 7-PVC Sheath

P/N: CL-23F-C7

Date	Author	Review	Approve	Version	Revision Declaration																																																																												
2016-03-03	Peterlau	Paulchan	JackLee	A0																																																																													
Content of the Data Sheet																																																																																	
Sheath Printing	---																																																																																
Customer reference																																																																																	
Category	S/FTP-CAT7-4P-PVC-AM30																																																																																
Test Standard	ISO/IEC 61156-5;EN 50288-4 ,YD/T1019																																																																																
Conductor	Material	SOLID-Bare Copper																																																																															
	Nom.O.D.(mm)	0.580	up	+0.005	down	-0.005																																																																											
Insulation	Material	Skin-foam-skin PE																																																																															
	Diameter	1.350±0.05 mm																																																																															
Inner Screening Material	Al/Mylar	Drain wire	TC 0.45																																																																														
Outer Screening Material	Aluminum-magnesium alloy	Coverage	≥30%																																																																														
Sheath	Thickness	0.60±0.05 mm																																																																															
	External O.D.	7.8±0.5 mm																																																																															
	Surface	Clean																																																																															
	Material	PVC(complies RoHS)																																																																															
	Color	According to the requires																																																																															
Surface Printing	Letter height	3.0±0.3mm																																																																															
	Color	Black																																																																															
	Print error & Space	≤±0.5%, 1m																																																																															
Core Color	1 White/Blue	2 White/Orange																																																																															
	3 White/Green	4 White/Brown																																																																															
Packing	Wooden Tray & Carton																																																																																
Wooden Tray dimension	According to the requires																																																																																
Packing length	305±1.0m																																																																																
Rip-cord	Yes																																																																																
Sheath Physical Properties	Before Aging	Tensile Strength (Mpa)	≥13.5																																																																														
		Elongation (%)	≥150																																																																														
	Aging Period (°C×hrs)	100°C×24h×7d																																																																															
	After Aging	Tensile Strength (Mpa)	≥12.5																																																																														
		Elongation (%)	≥125																																																																														
	Cold bend (-20±2°C×4h)	8xCable O.D., No visible cracks																																																																															
Electrical Characteristics (20°C)	Impedance(Ω) :	(1-100MHz)	100±15Ω																																																																														
		(100-250MHz)	100±18Ω																																																																														
		(250-600MHz)	100±25Ω																																																																														
		Delay Shew (ns/100m)	≤25																																																																														
		Velocity of Propagation (%)	74																																																																														
	unbalanced-to-ground capacitance (pf/100m) max	330																																																																															
	DC Resistance (Ω/100m) max	9.5																																																																															
	DC Conductor Resistance Unbalanc (%) max	2.0																																																																															
	Technical Performance (100m): <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Frequency (MHz)</th> <th>RL ≥dB</th> <th>ATT ≤dB</th> <th>NEXT ≥dB</th> <th>PHASE DELAY ≤ns</th> </tr> </thead> <tbody> <tr><td>4.0</td><td>23.0</td><td>3.74</td><td>78.0</td><td>552.0</td></tr> <tr><td>8.0</td><td>24.5</td><td>5.24</td><td>78.0</td><td>546.7</td></tr> <tr><td>10.0</td><td>25.0</td><td>5.86</td><td>78.0</td><td>545.4</td></tr> <tr><td>16.0</td><td>25.0</td><td>7.41</td><td>78.0</td><td>543.0</td></tr> <tr><td>20.0</td><td>25.0</td><td>8.29</td><td>78.0</td><td>542.0</td></tr> <tr><td>25.0</td><td>24.3</td><td>9.29</td><td>78.0</td><td>541.2</td></tr> <tr><td>31.25</td><td>23.6</td><td>10.41</td><td>78.0</td><td>540.4</td></tr> <tr><td>62.5</td><td>21.5</td><td>14.88</td><td>75.5</td><td>538.6</td></tr> <tr><td>100</td><td>20.1</td><td>19.02</td><td>72.4</td><td>537.6</td></tr> <tr><td>150</td><td>18.9</td><td>23.56</td><td>69.8</td><td>536.9</td></tr> <tr><td>200</td><td>18.0</td><td>27.47</td><td>67.9</td><td>536.5</td></tr> <tr><td>250</td><td>17.3</td><td>30.97</td><td>66.4</td><td>536.3</td></tr> <tr><td>300</td><td>17.3</td><td>34.19</td><td>65.2</td><td>536.1</td></tr> <tr><td>600</td><td>17.3</td><td>50.10</td><td>60.7</td><td>535.5</td></tr> </tbody> </table>						Frequency (MHz)	RL ≥dB	ATT ≤dB	NEXT ≥dB	PHASE DELAY ≤ns	4.0	23.0	3.74	78.0	552.0	8.0	24.5	5.24	78.0	546.7	10.0	25.0	5.86	78.0	545.4	16.0	25.0	7.41	78.0	543.0	20.0	25.0	8.29	78.0	542.0	25.0	24.3	9.29	78.0	541.2	31.25	23.6	10.41	78.0	540.4	62.5	21.5	14.88	75.5	538.6	100	20.1	19.02	72.4	537.6	150	18.9	23.56	69.8	536.9	200	18.0	27.47	67.9	536.5	250	17.3	30.97	66.4	536.3	300	17.3	34.19	65.2	536.1	600	17.3	50.10	60.7	535.5
	Frequency (MHz)	RL ≥dB	ATT ≤dB	NEXT ≥dB	PHASE DELAY ≤ns																																																																												
4.0	23.0	3.74	78.0	552.0																																																																													
8.0	24.5	5.24	78.0	546.7																																																																													
10.0	25.0	5.86	78.0	545.4																																																																													
16.0	25.0	7.41	78.0	543.0																																																																													
20.0	25.0	8.29	78.0	542.0																																																																													
25.0	24.3	9.29	78.0	541.2																																																																													
31.25	23.6	10.41	78.0	540.4																																																																													
62.5	21.5	14.88	75.5	538.6																																																																													
100	20.1	19.02	72.4	537.6																																																																													
150	18.9	23.56	69.8	536.9																																																																													
200	18.0	27.47	67.9	536.5																																																																													
250	17.3	30.97	66.4	536.3																																																																													
300	17.3	34.19	65.2	536.1																																																																													
600	17.3	50.10	60.7	535.5																																																																													
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Frequency (MHz)</th> <th>PSNEXT ≥dB</th> <th>ELFEXT ≥dB</th> <th>PSELFEXT ≥dB</th> </tr> </thead> <tbody> <tr><td>4</td><td>75.0</td><td>78.0</td><td>75.0</td></tr> <tr><td>8</td><td>75.0</td><td>75.9</td><td>72.9</td></tr> <tr><td>10</td><td>75.0</td><td>74.0</td><td>71.0</td></tr> <tr><td>16</td><td>75.0</td><td>69.9</td><td>66.9</td></tr> <tr><td>20</td><td>75.0</td><td>68.0</td><td>65.0</td></tr> <tr><td>25</td><td>75.0</td><td>66.0</td><td>63.0</td></tr> <tr><td>31.25</td><td>75.0</td><td>64.1</td><td>61.1</td></tr> <tr><td>62.5</td><td>72.5</td><td>58.1</td><td>55.1</td></tr> <tr><td>100</td><td>69.4</td><td>54.0</td><td>51.0</td></tr> <tr><td>150</td><td>66.8</td><td>50.2</td><td>47.2</td></tr> <tr><td>200</td><td>64.9</td><td>48.0</td><td>45.0</td></tr> <tr><td>250</td><td>63.4</td><td>46.0</td><td>43.0</td></tr> <tr><td>300</td><td>62.2</td><td>44.5</td><td>41.5</td></tr> <tr><td>600</td><td>57.7</td><td>38.4</td><td>35.4</td></tr> </tbody> </table>						Frequency (MHz)	PSNEXT ≥dB	ELFEXT ≥dB	PSELFEXT ≥dB	4	75.0	78.0	75.0	8	75.0	75.9	72.9	10	75.0	74.0	71.0	16	75.0	69.9	66.9	20	75.0	68.0	65.0	25	75.0	66.0	63.0	31.25	75.0	64.1	61.1	62.5	72.5	58.1	55.1	100	69.4	54.0	51.0	150	66.8	50.2	47.2	200	64.9	48.0	45.0	250	63.4	46.0	43.0	300	62.2	44.5	41.5	600	57.7	38.4	35.4																
Frequency (MHz)	PSNEXT ≥dB	ELFEXT ≥dB	PSELFEXT ≥dB																																																																														
4	75.0	78.0	75.0																																																																														
8	75.0	75.9	72.9																																																																														
10	75.0	74.0	71.0																																																																														
16	75.0	69.9	66.9																																																																														
20	75.0	68.0	65.0																																																																														
25	75.0	66.0	63.0																																																																														
31.25	75.0	64.1	61.1																																																																														
62.5	72.5	58.1	55.1																																																																														
100	69.4	54.0	51.0																																																																														
150	66.8	50.2	47.2																																																																														
200	64.9	48.0	45.0																																																																														
250	63.4	46.0	43.0																																																																														
300	62.2	44.5	41.5																																																																														
600	57.7	38.4	35.4																																																																														

